

The lightweight, low maintenance, rotary vane pump, has a sampling range of 5-30 LPM and is excellent for use in sampling asbestos (25mm cassettes), lead (37mm cassettes), and mold (*BUCK BioAire™* and Air-O-Cell® cassettes). This sampler also works for viable sampling (Single Stage Impactor) which requires a flow of 28.3 LPM. It is the best value in the market today, meeting OSHA and AHERA standards, and comes complete with inline filters, muffler jars, feet, handle, built in switch, and Rotameter.

**Features:**

- 5 - 30 LPM
- Also works for viable sampling (Single Stage Impactor) requiring a flow of 28.3 LPM.
- OSHA and AHERA compliant
- Lightweight-10 lbs
- Low maintenance

Flow rates:

- PCM Cassette - 3-15 LPM
- TEM Cassette - 3-10 LPM
- *Buck BioAire Cassette™* - 3-30 LPM
- Viable Impactor - 3-30 LPM

PRODUCT	DESCRIPTION
ALO-9803-88M	<i>BUCK</i> Rotary Vane Sampler with Flowmeter
ALO-9804-08	Light weight tripod
ALO-9804-08D	Cassette tripod adapter
ALO-9804-08E	Impactor/BioAire tripod adapter
APB-501000	B6 Single Stage Impactor for 100 x 15mm Petri Dish
APB-501010	Carry case for Microbial sampling kit components, hold additional sampling material.

Rev. 01-2006